

TW SERIES EXPANSION TANKS

TW SERIES
 POTABLE EXPANSION TANK
 150 PSIG WORKING PRESSURE



Certified to NSF/ANSI
 61-G and 372

CONSTRUCTION


Shell	Carbon Steel
Diaphragm	Butyl Rubber
Water Chamber	Polypropylene Liner
System Connection	Stainless Steel
Finish	Baked epoxy-polyester coating
Factory Precharge	38 PSIG

PERFORMANCE

Maximum Operating Temperature	200°F
Maximum Working Pressure	150 PSIG
Warranty	1 and 5-Year

TW SERIES - ONE YEAR LIMITED WARRANTY							
MODEL NUMBER	TANK VOLUME	MAX. ACCEPT VOLUME (GALS)		DIMENSIONS IN INCHES			SHIPPING WEIGHT (LBS)
		40 PSIG	60 PSIG	HEIGHT (A)	DIAMETER (B)	CONNECTION (MPT)	
TW 5-1	2.1	1.27	1.03	11	7.9	3/4	4.5
TW 12-1	4.8	3.05	2.19	13.7	10.6	3/4	8.2
TW SERIES - FIVE YEAR LIMITED WARRANTY							
TW 5-5	2.1	1.27	1.03	11	7.9	3/4	4.5
TW 12-5	4.8	3.05	2.19	13.7	10.6	3/4	8.2

All dimensions and weights are approximate.



JOB NAME: _____

P.O. NO: _____

ENGINEER: _____

SALES REP: _____

CONTRACTOR: _____

MODEL NO: _____